Fujitsu recommends Windows 8 Pro.



Data Sheet Fujitsu ESPRIMO E900 E90+ Desktop PC

Your Desktop PC Without Any Compromises

Fujitsu ESPRIMO E900 PCs give you the absolute highest PC manageability, performance and expandability. The optional Zero Noise PCs help you focus on your work and with 94% efficient power supply with 0-Watt technology, you'll also save on energy costs. The use of identical components ensures perfect infrastructure compatibility. At retirement, Fujitsu's distinctive EraseDisk function wipes your data securely.



Small form factor PC


Flexible desktop solution whatever the space required

Less than 13 liters volume, can be positioned vertically and horizontally

Green technology

Fujitsu's contribution to environmental protection for the continued existence of our planet

 Halogen-free printed circuit of mainboard and power supply, sophisticated product concept for the entire lifecycle



Low power consumption combined with top performance

■ 2nd generation Intel® Core™ processors with Turbo Boost 2.0 and Hyper-Threading technology and a power supply with up to 92% efficiency

System management

Simple system administration for complex IT infrastructures

■ Intel® vPro™ technology (depending on processor) and Fujitsu DeskView manageability tools

Quiet

Pleasant working environment due to an extremely quiet system

Innovative hardware design, optimized cooling concept































Page 1 / 9 www.fujitsu.com/fts/ESPRIMO

Components

Processor	Intel® Core™ i5-2400 processor (4 Cores / 4 Threads, 3.10 GHz, 6 MB, Intel® HD Graphics 2000)
	Intel® Core™ i3-2120 processor (2 Cores / 4 Threads, 3.30 GHz, 3 MB, Intel® HD Graphics 2000)
	Intel® Pentium® processor G850 (2 Cores / 2 Threads, 2.90 GHz, 3 MB, Intel® HD Graphics)
	Intel® vPro™ Logo with Intel® Core i5-2400, Intel® Core™ i5-2500 and Intel® Core™ i7-2600 processors.
Operating systems	
Operating system	Windows® 7 Home Basic (EM) 32-bit
	Windows® 7 Home Premium 64-bit
	Windows® 7 Professional 32-bit Windows® 7 Professional 64-bit
Operating system compatible	
Operating system compatible	openSUSE Linux Windows Vista®
	Windows® XP
	Citrix XenClient™ 2
Operating system notes	Limited Windows® XP support. Microsoft discontinued Windows® XP certification on system level, basic drivers via
Specific system notes	http://support.ts.fujitsu.com
Memory modules	2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1333 MHz, PC3-10600, DIMM
•	4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1333 MHz, PC3-10600, DIMM
Hard disk drives (internal)	SSD SATA III, 256 GB, 2.5-inch
	SSD SATA III, 128 GB, 2.5-inch
	SSD SATA II, 128 GB, 2.5-inch, FDE
	HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch
	HDD SATA III, 7200 rpm, 500 GB, 3.5-inch, business critical
	HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
	HDD SATA III, 7200 rpm, 250 GB, 3.5-inch
	HDD SATA II, 7200 rpm, 320 GB, 2.5-inch
	HDD SATA II, 7200 rpm, 160 GB, 2.5-inch
Hard disk notes	Up to 18 GB of HDD space is reserved for system recovery
Graphics add on cards (optional)	NVIDIA® Quadro® NVS 300 LP, 512 MB
	NVIDIA® GeForce® GT630 DisplayPort 2GB LP, 2 GB
	NVIDIA® GeForce® 605 DisplayPort 1GB LP, 1 GB
	LFH59/ 2x DVI-I adapter cable
	LFH59/ 2x DP adapter cable
	DP to DVI-D (single link) Adapter Cable
	2nd NVIDIA® Quadro® NVS 300 LP, 512 MB
Orives (optional)	BD Triple Writer SATA slim (tray)
(-)	DVD-ROM
	DVD Super Multi
	MCR 24in1 & USB 3.0 front con., 3.5"
	MultiCard Reader 20in1 USB 3.0 front con., 3.5-Inch
	MultiCard Reader 24in1 USB 2.0 3.5"
nterface add on cards/components (optional)	
	WLAN III, 802.11g/Draft-n (Windows only, dedicated regions only)
	Parallel Interface
	Parallel Interface Gigabit Ethernet PCle x1, DS
	Gigabit Ethernet PCle x1, DS

Dago unit	ECDDIMO EGGG FOO
Base unit	ESPRIMO E900 E90+
Mainboard	
Mainboard type	D3062
Formfactor	μATX
Chipset	Intel® Q67
Processor socket	LGA 1155
Processor quantity maximum	1
Memory slots	4 DIMM (DDR3)
Supported capacity RAM (max.)	32 GB
Memory frequency	1333 MHz
Memory notes	Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be
	the same. > 16 GB support with future memory modules
LAN	10/100/1000 MBit/s Intel® 82579 LM
BIOS version	AMI Aptio 4.6
BIOS features	BIOS Flash EPROM update by software
bios icatales	Recovery BIOS
	Unified Extensible Firmware Interface (UEFI)
	FastOn
Audio codec	Conexant CX20642
Audio features	Internal speaker supports audio playback, High Definition audio, 5.1 surround sound
I/O controller on board	
Serial ATA total	6
thereof SATA III	2
thereof eSATA	2 (optional)
Controller functions	Serial ATA II (3 Gbit)
	Serial ATA III (6 Gbit)
	NCQ
	AHCI
	Raid 1/0
Interfaces	
Audio: line-in	1
Audio: line-in / microphone	1
Audio: line-out	1
Front audio: microphone	1
Front audio: headphone	1
USB 2.0 total	14
USB 3.0 total	optional
USB front	4
USB rear	8
USB internal	2
VGA	1 (via DVI to VGA adapter, part of shipment)
DisplayPort	1
DVI	1 (DVI-I)
Serial (RS-232)	1 (9pin, 16 byte FIFO, 16550 compatible)
Mouse / Keyboard (PS/2)	2
Ethernet (RJ-45)	1
Parallel	1 (optional) (25pin with EPP and ECP)
eSATA	1 (optional)
Interface Module notes	Anytime USB charge functionality

Page 3 / 9 www.fujitsu.com/fts/ESPRIMO

Input davice / company	
Input device / components	0-5-1000 55-1-1
	Optical USB tilt wheel mouse
Input devices (optional)	Optical USB/PS2 tilt wheel mouse KBPC PX ECO
	Mouse M440 ECO
Drive bays	
Drive bays total	3
3.5-inch internal bays	1
3.5-inch external bays	1
5.25-inch external bays	1
Drive bay notes	optional external bay as internal 3,5"
Slots	
PCI-Express 2.0 x16	1 x (200 mm / 7.87 inch) Low profile
PCI-Express 2.0 x4 (mech. x16)	1 x (200 mm / 7.87 inch) Low profile
PCI-Express x1	1 x (174 mm / 6.85 inch) Low profile
PCI (32-bit / 33 MHz)	1 x (174 mm / 6.85 inch) Low profile
Slots optional configuration	or 2x PCI full high via Riser
Graphics on board	
Graphics brand name	Intel® HD Graphics or HD Graphics 2000 (depending on CPU)
Shared video memory	up to 1759 MB
TFT resolution (VGA)	1024 x 768 pixel
	1280 x 1024 pixel
	1360 x 768 pixel
	1440 x 900 pixel
	1600 x 900 pixel
	1600 x 1200 pixel
	1680 x 1050 pixel
	1920 x 1080 pixel
TFT resolution (DVI)	1920 x 1200 pixel 1360 x 768 pixel
Ti i lesolution (DVI)	1440 x 900 pixel
	1600 x 900 pixel
	1680 x 1050 pixel
	1920 x 1080 pixel
	1920 x 1200 pixel
TFT resolution (DisplayPort)	1360 x 768 pixel
	1440 x 900 pixel
	1600 x 900 pixel
	1680 x 1050 pixel
	1920 x 1080 pixel
	1920 x 1200 pixel 2560 x 1440 pixel
	2560 x 1600 pixel
Graphics features	Dual display support
diapnics leadures	DirectX 10.1
	HDCP support
	OpenGL® 2.1
	For multi monitoring mode, graphics card and integrated graphics run in parallel (Microsoft® Windows 7® only)
Graphics notes	Tested resolutions, depending on display type additional resolutions and frequencies possible
	Shared memory depending on main memory size and operating system
	Resolution (color depth up to 32 Bit/pixel)
	For TFT we recommend using 60Hz
Electrical values	
Power efficiency note	power supply efficiency (at 230V; 20% / 50% / 100% load) : 88% / 92% / 91%
Rated voltage range	100 V - 240 V

Page 4 / 9 www.fujitsu.com/fts/ESPRIMO

Electrical values	
Rated frequency range	50 Hz - 60 Hz
Operating voltage range	90 V - 264 V
Operating line frequency range	47 Hz - 63 Hz
Max. output of single power supply	280 W
Power factor correction/active power	active
Monitor outlet	Switched
Power consumption	
Power consumption note	See white paper Energy Consumption
Link to Energy White Paper	http://docs.ts.fujitsu.com/dl.aspx?id=7a7269cb-b7c8-43ec-bff0-4ac567640f1b
Heat dissipation	
Heat dissipation notes	See white paper Energy Consumption
Noise for standard configuration (HDD,	
Noise emission	According to ISO9296
Related Processors for noise	Intel® Core™ i5 2400
Noise Operation mode 1: ODD load	4.2 B/ 28 dB(A)
(Blue angel requirement)	4.2 bi 20 db(r)
Noise Operation mode 2: HDD load	3.4 B/ 19 dB(A)
(Blue angel requirement)	
Noise Operation mode 3: CPU 90% load	3.6 B/ 21 dB(A)
(Blue angel requirement)	
Noise Operation mode 4: High load	3.8 B/ 24 dB(A)
Noise Operation mode 5: Office	3.3 B/ 19 dB(A)
applications 2.0	
Idle mode (Blue Angel requirement)	3.3 B/ 19 dB(A)
Idle mode (Blue Angel requirement) Noise notes / description	3.3 B/ 19 dB(A) A weighted sound power level Lwad (in B) / workplace related A-weighted sound pressure level LpAm (in dB(A)), Bystander position
	A weighted sound power level Lwad (in B) / workplace related A-weighted sound pressure level LpAm (in dB(A)),
Noise notes / description	A weighted sound power level Lwad (in B) / workplace related A-weighted sound pressure level LpAm (in dB(A)),
Noise notes / description Dimensions / Weight / Environmental	A weighted sound power level Lwad (in B) / workplace related A-weighted sound pressure level LpAm (in dB(A)), Bystander position
Noise notes / description Dimensions / Weight / Environmental	A weighted sound power level Lwad (in B) / workplace related A-weighted sound pressure level LpAm (in dB(A)), Bystander position 340 x 382 x 98 mm
Noise notes / description Dimensions / Weight / Environmental Dimensions (W x D x H)	A weighted sound power level Lwad (in B) / workplace related A-weighted sound pressure level LpAm (in dB(A)), Bystander position 340 x 382 x 98 mm 13.39 x 15.04 x 3.86 inch
Noise notes / description Dimensions / Weight / Environmental Dimensions (W x D x H) Operating position	A weighted sound power level Lwad (in B) / workplace related A-weighted sound pressure level LpAm (in dB(A)), Bystander position 340 x 382 x 98 mm 13.39 x 15.04 x 3.86 inch horizontal / vertical (optional, feet needed)
Noise notes / description Dimensions / Weight / Environmental Dimensions (W x D x H) Operating position Weight	A weighted sound power level Lwad (in B) / workplace related A-weighted sound pressure level LpAm (in dB(A)), Bystander position 340 x 382 x 98 mm 13.39 x 15.04 x 3.86 inch horizontal / vertical (optional, feet needed) 10 kg
Noise notes / description Dimensions / Weight / Environmental Dimensions (W x D x H) Operating position Weight Weight (lbs)	A weighted sound power level Lwad (in B) / workplace related A-weighted sound pressure level LpAm (in dB(A)), Bystander position 340 x 382 x 98 mm 13.39 x 15.04 x 3.86 inch horizontal / vertical (optional, feet needed) 10 kg 22.05 lbs
Noise notes / description Dimensions / Weight / Environmental Dimensions (W x D x H) Operating position Weight Weight (lbs) Weight notes	A weighted sound power level Lwad (in B) / workplace related A-weighted sound pressure level LpAm (in dB(A)), Bystander position 340 x 382 x 98 mm 13.39 x 15.04 x 3.86 inch horizontal / vertical (optional, feet needed) 10 kg 22.05 lbs Actual weight may vary depending on configuration
Noise notes / description Dimensions / Weight / Environmental Dimensions (W x D x H) Operating position Weight Weight (lbs) Weight notes Operating ambient temperature	A weighted sound power level Lwad (in B) / workplace related A-weighted sound pressure level LpAm (in dB(A)), Bystander position 340 x 382 x 98 mm 13.39 x 15.04 x 3.86 inch horizontal / vertical (optional, feet needed) 10 kg 22.05 lbs Actual weight may vary depending on configuration
Noise notes / description Dimensions / Weight / Environmental Dimensions (W x D x H) Operating position Weight Weight (lbs) Weight notes Operating ambient temperature Compliance	A weighted sound power level Lwad (in B) / workplace related A-weighted sound pressure level LpAm (in dB(A)), Bystander position 340 x 382 x 98 mm 13.39 x 15.04 x 3.86 inch horizontal / vertical (optional, feet needed) 10 kg 22.05 lbs Actual weight may vary depending on configuration 10 - 35°C (50 - 95°F)
Noise notes / description Dimensions / Weight / Environmental Dimensions (W x D x H) Operating position Weight Weight (lbs) Weight notes Operating ambient temperature Compliance Product	A weighted sound power level Lwad (in B) / workplace related A-weighted sound pressure level LpAm (in dB(A)), Bystander position 340 x 382 x 98 mm 13.39 x 15.04 x 3.86 inch horizontal / vertical (optional, feet needed) 10 kg 22.05 lbs Actual weight may vary depending on configuration 10 - 35°C (50 - 95°F) ESPRIMO E900
Noise notes / description Dimensions / Weight / Environmental Dimensions (W x D x H) Operating position Weight Weight (lbs) Weight notes Operating ambient temperature Compliance Product Model	A weighted sound power level Lwad (in B) / workplace related A-weighted sound pressure level LpAm (in dB(A)), Bystander position 340 x 382 x 98 mm 13.39 x 15.04 x 3.86 inch horizontal / vertical (optional, feet needed) 10 kg 22.05 lbs Actual weight may vary depending on configuration 10 - 35°C (50 - 95°F) ESPRIMO E900 DT8-3062
Noise notes / description Dimensions / Weight / Environmental Dimensions (W x D x H) Operating position Weight Weight (lbs) Weight notes Operating ambient temperature Compliance Product Model Germany	A weighted sound power level Lwad (in B) / workplace related A-weighted sound pressure level LpAm (in dB(A)), Bystander position 340 x 382 x 98 mm 13.39 x 15.04 x 3.86 inch horizontal / vertical (optional, feet needed) 10 kg 22.05 lbs Actual weight may vary depending on configuration 10 - 35°C (50 - 95°F) ESPRIMO E900 DT8-3062 TÜV GS
Noise notes / description Dimensions / Weight / Environmental Dimensions (W x D x H) Operating position Weight Weight (lbs) Weight notes Operating ambient temperature Compliance Product Model Germany	A weighted sound power level Lwad (in B) / workplace related A-weighted sound pressure level LpAm (in dB(A)), Bystander position 340 x 382 x 98 mm 13.39 x 15.04 x 3.86 inch horizontal / vertical (optional, feet needed) 10 kg 22.05 lbs Actual weight may vary depending on configuration 10 - 35°C (50 - 95°F) ESPRIMO E900 DT8-3062 TÜV GS CE
Noise notes / description Dimensions / Weight / Environmental Dimensions (W x D x H) Operating position Weight Weight (lbs) Weight notes Operating ambient temperature Compliance Product Model Germany Europe USA/Canada	A weighted sound power level Lwad (in B) / workplace related A-weighted sound pressure level LpAm (in dB(A)), Bystander position 340 x 382 x 98 mm 13.39 x 15.04 x 3.86 inch horizontal / vertical (optional, feet needed) 10 kg 22.05 lbs Actual weight may vary depending on configuration 10 - 35°C (50 - 95°F) ESPRIMO E900 DT8-3062 TÜV GS CE Nordic Swan FCC Class B cCSAus
Noise notes / description Dimensions / Weight / Environmental Dimensions (W x D x H) Operating position Weight Weight (lbs) Weight notes Operating ambient temperature Compliance Product Model Germany Europe	A weighted sound power level Lwad (in B) / workplace related A-weighted sound pressure level LpAm (in dB(A)), Bystander position 340 x 382 x 98 mm 13.39 x 15.04 x 3.86 inch horizontal / vertical (optional, feet needed) 10 kg 22.05 lbs Actual weight may vary depending on configuration 10 - 35°C (50 - 95°F) ESPRIMO E900 DT8-3062 TÜV GS CE Nordic Swan FCC Class B CCSAus ROHS (Restriction of hazardous substances)
Noise notes / description Dimensions / Weight / Environmental Dimensions (W x D x H) Operating position Weight Weight (lbs) Weight notes Operating ambient temperature Compliance Product Model Germany Europe USA/Canada	A weighted sound power level Lwad (in B) / workplace related A-weighted sound pressure level LpAm (in dB(A)), Bystander position 340 x 382 x 98 mm 13.39 x 15.04 x 3.86 inch horizontal / vertical (optional, feet needed) 10 kg 22.05 lbs Actual weight may vary depending on configuration 10 - 35°C (50 - 95°F) ESPRIMO E900 DT8-3062 TÜV GS CE Nordic Swan FCC Class B CCSAus ROHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment)
Noise notes / description Dimensions / Weight / Environmental Dimensions (W x D x H) Operating position Weight Weight (lbs) Weight notes Operating ambient temperature Compliance Product Model Germany Europe USA/Canada	A weighted sound power level Lwad (in B) / workplace related A-weighted sound pressure level LpAm (in dB(A)), Bystander position 340 x 382 x 98 mm 13.39 x 15.04 x 3.86 inch horizontal / vertical (optional, feet needed) 10 kg 22.05 lbs Actual weight may vary depending on configuration 10 - 35°C (50 - 95°F) ESPRIMO E900 DT8-3062 TÜV GS CE Nordic Swan FCC Class B cCSAus ROHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL)
Noise notes / description Dimensions / Weight / Environmental Dimensions (W x D x H) Operating position Weight Weight (lbs) Weight notes Operating ambient temperature Compliance Product Model Germany Europe USA/Canada	A weighted sound power level Lwad (in B) / workplace related A-weighted sound pressure level LpAm (in dB(A)), Bystander position 340 x 382 x 98 mm 13.39 x 15.04 x 3.86 inch horizontal / vertical (optional, feet needed) 10 kg 22.05 lbs Actual weight may vary depending on configuration 10 - 35°C (50 - 95°F) ESPRIMO E900 DTB-3062 TÜV GS CE Nordic Swan FCC Class B cCSAus ROHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR®
Noise notes / description Dimensions / Weight / Environmental Dimensions (W x D x H) Operating position Weight Weight (lbs) Weight notes Operating ambient temperature Compliance Product Model Germany Europe USA/Canada	A weighted sound power level Lwad (in B) / workplace related A-weighted sound pressure level LpAm (in dB(A)), Bystander position 340 x 382 x 98 mm 13.39 x 15.04 x 3.86 inch horizontal / vertical (optional, feet needed) 10 kg 22.05 lbs Actual weight may vary depending on configuration 10 - 35°C (50 - 95°F) ESPRIMO E900 DT8-3062 TÜV GS CE Nordic Swan FCC Class B cCSAus ROHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL)

Page 5 / 9 www.fujitsu.com/fts/ESPRIMO

Additional Software	
Additional software (preinstalled)	Nero Essentials S (burning software)
(р,	Fujitsu Recovery (Hard Disk Based Recovery)
	Norton Internet Security (incl. Firewall) 60 days version
	Don't forget Office.
Additional software (optional)	Recovery DVD for Windows®
Additional software (optional)	Drivers & Utilities DVD (DUDVD)
	CyberLink PowerDVD BD (playback software for Blu-ray Disc™, only with Blu-ray Disc™ drive / Blu-ray playback is not
	supported under Windows XP if the system runs on Intel onboard graphics)
Miscellaneous	
	Keyboard on (Special Fujitsu keyboard required)
	Thermal management
	Extended lifetime
Compatibility (references)	
	DMI 2.0
	PC 2001
	WMI 1.5
	USB 2.0
	SMBIOS
 Manageability	
Manageability technology	DeskUpdate Driver management
Manageability technology	PXE 2.1 Boot code
	Wake up from S5 (off mode)
	Intrusion switch (optional)
	iAMT 7.0
NA	WoL (Wake on LAN)
Manageability software	DeskView Client
	DeskView Instant BIOS Management
	DeskView Integration for Symantec Management Platform
DeskView components	Inventory Management
	BIOS Management
	Driver Management
	Security Management
	Alarm Management
Manageability link	http://ts.fujitsu.com/manageability
Security	
System protection	Kensington Lock support
, .	Eye for padlock
	Optional: Integrated cabinet lock
Audit proof protection	EraseDisk (optional)
	Boot sector virus protection
	Write protect option for the Flash EPROM
	Embedded security (TPM 1.2)
	Control of all USB interfaces
	External USB ports can be disabled separately
	Control of external interfaces
	User and supervisor BIOS password
Access protection	Hard disk password
	Optional: Access protection via external SmartCard reader Optional: Access protection via internal SmartCard reader
	optional. Access protection via internal sillaticato leader
Serviceability	
	EasyFix
	EasyChange for HDD EasyChange for optical drives

Page 6 / 9 www.fujitsu.com/fts/ESPRIMO

Packaging information	
Packaging dimension (mm)	467 x 265 x 540 mm
Packaging dimension (inch)	18.39 x 10.43 x 21.26 inch
Max. quantity / pallet	28
Material - Weight (g) Carton	1140 g
Material - Weight (lbs) Carton	2.51 lbs
Material - Weight (g) EPS / PS	180 g
Material - Weight (lbs) EPS / PS	0.4 lbs
Material - Weight (g) PE	60 g
Material - Weight (lbs) PE	0.13 lbs
Packaging notes	printed user documentation is bleached in chlorine free process
Warranty	
Standard Warranty	3 years
Service level	Bring-In / On-Site Service (depending on country)
Maintenance and Support Services - th	ne perfect extension
Recommended Service	5x9, Response Time: Next Business Day
Spare Parts availability	5 years
Service Weblink	http://www.fujitsu.com/fts/services/support/index.html

Recommended Accessories

Wireless Keyboard Set LX900



The Wireless Keyboard LX900 is a top of the line desktop solution for lifestyle orientated customers, who want only the best for their desk. This superb keyboard set with offers ambitious users more functions, security and better features than a conventional interface device. It even includes 2.4 GHz technology and 128 AES encryption for security.

S26381-K564-L4** (**: Country specific variation)

Keyboard KBPC PX ECO



Fujitsu's KBPC PX ECO keyboard is the perfect contribution to Green IT. The keyboard is made out of 45% renewable raw material and comes with a PVC country specific variation) free USB cable. In addition, the KBPC PX ECO offers first class comfort and ergonomics. It attracts attention with its impressive modern design and

S26381-K341-L1** (**:

SOUNDSYSTEM DS P2100 Tube



Taking inspiration from a hi-fi sound bar, the Fujitsu SOUNDSYSTEM DS P2100 Tube presents you with living room design art pieces for acoustic enjoyment. Automatic amplifier adjustment ensures extremely low distortion, which will protect the hearing and avoid speaker damage. With new convenient volume control- Fade-in & Fade-out audio effect. The small & robust satellite speaker is decorated with a deluxe piano finish and the aluminum tube is adorned with a fine print of an exotic motif at its base.

Order Code: S26391-F7128-L500

SOUNDSYSTEM DS E2000 Air



The new more powerful SOUNDSYSTEM DS E2000 Air gives you impressive, well-balanced sound throughout the frequency band. It is an unbeatable USB speaker set with a surprisingly small form factor. The robust satellite speakers are decorated with a deluxe piano finish and the base is adorned with warm ambient lighting.

S26391-F7128-L600

Order Code:

WebCam 130 HD2



With the most advanced HD (High Definition / 720p) recording feature and Order Code: widescreen video format (16:9 and 16:10), WebCam 130 HD2 can capture S26391-F7136-L5 up to 30 frame rate per second, close up to HD/720p quality video. Even more: 1-Click-Upload makes the video uploading to YouTube in a snap! With smart clip for notebook & LCD display it is easy to install on any device you

Page 7 / 9 www.fujitsu.com/fts/ESPRIMO

HS S2000NC Headset



The HS S2000NC Headset offers more than current headsets. Besides superb Order Code: sound quality, the headset provides an impressive feature: a button to S26391-F7139-L3 switch off noise and disburden your ears of unwanted noise level. Thanks to a special technology based on wave inversion this headset reduces unwanted noise by up to 70 % for a quieter audio experience. The sponge cushion specially made by BioProtein ensures optimum comfort for long hours travelling by rail or air.

HS E2000 Communicator Headset



The Fujitsu HS E2000 Communicator headset allows you to use your personal computer for Voice over IP (VoIP) in stereo audio quality. This premium headset is designed to provide superb audio quality and comfort for the telephony, internet chat, speech recognition, video conferencing and multimedia applications.

Order Code: S26391-F7139-L5

CELVIN® Drive D100



The CELVIN® Drive D100 is a highly reliable external storage device with a standard USB-interface for easy Plug & Play use with a notebook or PC. It is S26341-F103-L118 also easy to set up additional home network capacity by connecting it with dedicated routers or NAS devices.

MYUSBS A910



The high-quality MYUSBS A910 is a high-class, cost-efficient storage device, Order Code: which can be used with any standard USB port. Available in different storage capacities the stylish MYUSBS A910 is perfect for a wide range of application areas. This extremely easy to use Pluq & Play device fits in any pocket.

S26391-F6048-L208

Page 8 / 9 www.fujitsu.com/fts/ESPRIMO

More information

Fujitsu OPTIMIZATION Services

In addition to Fujitsu ESPRIMO E900 E90+, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu ESPRIMO E900 E90+, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/fts/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at http://www.fujitsu.com/global/about/environment/



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/

Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU Technology Solutions Website: www.fujitsu.com/fts 2012-11-06 CE-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/terms

Copyright © Fujitsu Technology Solutions