

Fujitsu recommends Windows® 7.

Data Sheet

Fujitsu ESPRIMO E910 E90+ Desktop PC

Preliminary Data sheet / For internal use only

Company confidential

Your Desktop PC Without Any Compromises

Fujitsu ESPRIMO E910 PCs give you the absolute highest PC manageability, performance and expandability. The optional Zero Noise PCs help you focus on your work and with 94% efficient power supply with 0-Watt technology, you'll also save on energy costs. The use of identical components ensures perfect infrastructure compatibility. At retirement, Fujitsu's distinctive EraseDisk function wipes your data securely.



Small form factor PC

Flexible desktop solution whatever the space required

- Less than 13 liters volume, can be positioned vertically and horizontally

Environmentally conscious product with ENERGY STAR® certification

Your contribution to environmental protection for the continued existence of our planet

- Halogen-free printed circuit of mainboard and power supply, sophisticated product concept for the entire lifecycle



Highest energy efficiency coupled with intelligent performance

Low power consumption combined with top performance

- 3rd generation Intel® Core™ processors with Turbo Boost and Hyper-Threading technology and a power supply with up to 92% efficiency

System management


Simple system administration for complex IT infrastructures

- Intel® vPro™ technology (depending on processor)

Quiet

Pleasant working environment due to an extremely quiet system

- Innovative hardware design, optimized cooling concept



Components

| | |
|---|---|
| | Intel® vPro™ Logo with Intel® Core i5 and Core i7 processors |
| Processor | Intel® Core™ i7-3770 processor (4 Cores / 8 Threads, 3.40 GHz, 8 MB, Intel® HD Graphics 4000) |
| | Intel® Core™ i5-3570 processor (4 Cores / 4 Threads, 3.40 GHz, 6 MB, Intel® HD Graphics 2500) |
| | Intel® Core™ i5-3550 processor (4 Cores / 4 Threads, 3.30 GHz, 6 MB, Intel® HD Graphics 2500) |
| | Intel® Core™ i5-3470 processor (4 Cores / 4 Threads, 3.20 GHz, 6 MB, Intel® HD Graphics 2500) |
| | Intel® Core™ i5-2400 processor (4 Cores / 4 Threads, 3.10 GHz, 6 MB, Intel® HD Graphics 2000) |
| | Intel® Core™ i3-2120 processor (2 Cores / 4 Threads, 3.30 GHz, 3 MB, Intel® HD Graphics 2000) |
| | Intel® Pentium® processor G850 (2 Cores / 2 Threads, 2.90 GHz, 3 MB, Intel® HD Graphics) |
| | Intel® Pentium® processor G630 (2 Cores / 2 Threads, 2.70 GHz, 3 MB, Intel® HD Graphics) |
| | Intel® Celeron® processor G530 (2 Cores / 2 Threads, 2.40 GHz, 2 MB, Intel® HD Graphics) |
| Operating systems | |
| Operating system | Genuine Windows® 7 Home Basic (EM) 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit |
| Operating system compatible | openSUSE Linux Genuine Windows® XP |
| Operating system notes | Limited Windows® XP support. Microsoft discontinued Windows® XP certification on system level, basic drivers via http://support.ts.fujitsu.com |
| Memory modules | 2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM 4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM 8 GB (1 module(s) 8 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM |
| Hard disk drives (internal) | SSD SATA III, 128 GB, 2.5-inch HDD SATA III, 7200 rpm, 2000 GB, 3.5-inch HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch HDD SATA III, 7200 rpm, 500 GB, 3.5-inch, business critical HDD SATA III, 7200 rpm, 500 GB, 3.5-inch HDD SATA III, 7200 rpm, 250 GB, 3.5-inch HDD SATA II, 7200 rpm, 320 GB, 2.5-inch HDD SATA II, 7200 rpm, 160 GB, 2.5-inch |
| Hard disk notes | Up to 18 GB of HDD space is reserved for system recovery |
| Graphics add on cards (optional) | NVIDIA® Quadro® NVS 300 LP, 512 MB NVIDIA® GeForce® GT630 DisplayPort 2GB LP, 2 GB NVIDIA® GeForce® 605 DisplayPort 1GB LP, 1 GB LFH59/ 2x DVI-I adapter cable LFH59/ 2x DP adapter cable DP to DVI-D (single link) Adapter Cable 2nd NVIDIA® Quadro® NVS 300 LP, 512 MB |
| Drives (optional) | BD Triple Writer SATA slim (tray) DVD-ROM DVD Super Multi MultiCard Reader 16in1, USB 2.0, 3.5" |

**Interface add on cards/components
(optional)**

WLAN III, 802.11g/Draft-n (Windows only)
 Parallel Interface
 Gigabit Ethernet PCIe x1, DS
 eSATA Interface
 Dual serial card PCIe x1, powered
 Dual serial card PCIe x1

Base unit ESPRIMO E910 E90+

Mainboard

| | |
|--------------------------------------|---|
| Mainboard type | D3162 |
| Formfactor | µATX |
| Chipset | Intel® Q77 |
| Processor socket | LGA 1155 |
| Processor quantity maximum | 1 |
| Memory slots | 4 DIMM (DDR3) |
| Supported capacity RAM (max.) | 32 GB |
| Memory frequency | 1600 MHz |
| Memory notes | Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same. |
| LAN | 10/100/1000 MBit/s Intel® 82579 LM |
| BIOS version | AMI Aptio 4.6 |
| BIOS features | BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI) |
| Audio codec | Conexant CX20642 |
| Audio features | Internal speaker supports audio playback, High Definition audio, 5.1 surround sound |

I/O controller on board

| | |
|-----------------------------|---|
| Serial ATA total | 6 |
| thereof SATA III | 2 |
| thereof eSATA | 2 (optional) |
| Controller functions | Serial ATA II (3 Gbit) Serial ATA III (6 Gbit) NCQ AHCI Raid 1/0 Intel® Smart Response Technology (depending on CPU) |

Interfaces

| | |
|------------------------------------|--|
| Audio: line-in | 1 |
| Audio: line-in / microphone | 1 |
| Audio: line-out | 1 |
| Front audio: headphone | 1 |
| USB 2.0 total | 10 |
| USB 3.0 total | 4 |
| USB front | 4x 2.0 or 2x 2.0/ 2x 3.0 |
| USB rear | 6x 2.0 / 2x 3.0 |
| USB internal | 2 |
| VGA | 1 (via DVI to VGA adapter, part of shipment) |
| DisplayPort | 1 |
| DVI | 1 (DVI-I) |
| Serial (RS-232) | 1 (9pin, 16 byte FIFO, 16550 compatible) |
| Mouse / Keyboard (PS/2) | 2 |

Interfaces

| | |
|------------------------|---------------------------------------|
| Ethernet (RJ-45) | 1 |
| Parallel | 1 (optional) (25pin with EPP and ECP) |
| eSATA | 1 (optional) |
| Interface Module notes | Anytime USB charge functionality |

Input device / components

| | |
|--------------------------|--|
| Input devices (optional) | Optical USB wheel mouse Optical USB/PS2 tilt wheel mouse KBPC PX ECO Mouse M440 ECO |
|--------------------------|--|

Drive bays

| | |
|-------------------------|--|
| Drive bays total | 3 |
| 3.5-inch internal bays | 1 |
| 3.5-inch external bays | 1 |
| 5.25-inch external bays | 1 |
| Drive bay notes | optional external bay as internal 3,5" |

Slots

| | |
|--------------------------------|-------------------------------|
| PCI-Express 3.0 x16 | 1 x (200 mm) Low profile |
| PCI-Express 2.0 x4 (mech. x16) | 1 x (200 mm) Low profile |
| PCI-Express x1 | 1 x (174 mm) Low profile |
| PCI (32-bit / 33 MHz) | 1 x (174 mm) Low profile |
| Slots optional configuration | or 2x PCI full high via Riser |

Graphics on board

| | |
|------------------------------|---|
| Graphics brand name | Intel® HD Graphics, HD Graphics 2000, HD Graphics 2500, HD Graphics 4000 (depending on CPU) |
| Shared video memory | up to 1759 MB |
| TFT resolution (VGA) | 1024 x 768 pixel 1280 x 1024 pixel 1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1600 x 1200 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel |
| TFT resolution (DVI) | 1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel |
| TFT resolution (DisplayPort) | 1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel 2560 x 1440 pixel 2560 x 1600 pixel |

Graphics features

Dual display support
DirectX® 10.1 or DirectX® 11 (depending on CPU)
HDCP support
Open GL® 3.1 (depending on CPU)
Open CL™ 1.1 (depending on CPU)
For multi monitoring mode, graphics card and integrated graphics run in parallel (Microsoft® Windows 7® only)

Graphics on board

| | |
|-----------------------|---|
| Graphics notes | Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz |
|-----------------------|---|

Electrical values

| | |
|---|--|
| Power efficiency note | power supply efficiency (at 230V; 20% / 50% / 100% load) : 88% / 92% / 91% |
| Rated voltage range | 100 V - 240 V |
| Rated frequency range | 50 Hz - 60 Hz |
| Operating voltage range | 90 V - 264 V |
| Operating line frequency range | 47 Hz - 63 Hz |
| Max. output of single power supply | 280 W |
| Power factor correction/active power | active |
| Monitor outlet | Switched |

Power consumption

| | |
|-------------------------------|------------------------------------|
| Power consumption note | See white paper Energy Consumption |
|-------------------------------|------------------------------------|

Heat dissipation

| | |
|-------------------------------|------------------------------------|
| Heat dissipation notes | See white paper Energy Consumption |
|-------------------------------|------------------------------------|

Noise for standard configuration (HDD, ODD)

| | |
|--|--|
| Noise emission | According to ISO9296 |
| Related Processors for noise | tbd |
| Noise Operation mode 1: ODD load (Blue angel requirement) | tbd |
| Noise Operation mode 2: HDD load (Blue angel requirement) | tbd |
| Noise Operation mode 4: High load | tbd |
| Noise Operation mode 5: Office applications 2.0 | tbd |
| Idle mode (Blue Angel requirement) | tbd |
| Noise notes / description | A weighted sound power level Lwad (in B) / workplace related A-weighted sound pressure level LpAm (in dB(A)), Bystander position |

Dimensions / Weight / Environmental

| | |
|--------------------------------------|---|
| Dimensions (W x D x H) | 340 x 382 x 98 mm |
| Operating position | Vertical / horizontal (optional, feet needed) |
| Weight | approx. 10 kg |
| Weight notes | Actual weight may vary depending on configuration |
| Operating ambient temperature | 10 - 35°C |

Compliance

| | |
|------------------------|--|
| Product | ESPRIMO E910 |
| Model | DT8-3162 |
| Germany | TÜV GS |
| Europe | CE Nordic Swan in progress |
| USA/Canada | FCC Class B cCSAus |
| Global | RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® in progress EPEAT® in progress (dedicated regions) |
| Compliance link | https://sp.ts.fujitsu.com/sites/certificates/ |

Additional Software

Additional software (preinstalled) Nero Essentials S (burning software)
 Fujitsu Recovery (Hard Disk Based Recovery)
 Norton Internet Security (incl. Firewall) 60 days version
 Microsoft® Office Starter: reduced-functionality Word and Excel® only, with advertising. No PowerPoint® or Outlook®. Buy Office 2010 to use the full-featured software.

Additional software (optional) Recovery DVD for Windows®
 Drivers & Utilities DVD (DUDVD)
 CyberLink PowerDVD BD (playback software for Blu-ray Disc™, only with Blu-ray Disc™ drive / Blu-ray playback is not supported under Windows XP if the system runs on Intel onboard graphics)
 Nero 10 Essentials XL

Miscellaneous

Keyboard on (Special Fujitsu keyboard required)
 Thermal management
 Extended lifetime

Compatibility (references)

DMI 2.0
 PC 2001
 WMI 1.5
 USB 2.0
 SMBIOS

Manageability

Manageability technology DeskUpdate Driver management
 PXE 2.1 Boot code
 Wake up from S5 (off mode)
 Intrusion switch (optional)
 iAMT 8.0 (depending on CPU)

Manageability software DeskView 10.x client management including:

DeskView components On/Offline remote client management
 Detailed system inventory management and reports
 BIOS Management
 Remote power management
 System notifications
 Security Remote Control
 DeskView Helpdesk Integration
 WoL (Wake on LAN)

Manageability link <http://ts.fujitsu.com/manageability>
<http://www.altiris.com/fujitsu>

Security

System protection Kensington Lock support
 Eye for padlock
 Optional: Integrated cabinet lock

Audit proof protection EraseDisk (optional)
 Boot sector virus protection
 Write protect option for the Flash EPROM
 Embedded security (TPM 1.2)
 Control of all USB interfaces
 External USB ports can be disabled separately
 Control of external interfaces

Access protection User and supervisor BIOS password
 Hard disk password
 Optional: Access protection via external SmartCard reader
 Optional: Access protection via internal SmartCard reader

Serviceability

EasyFix
EasyChange for HDD
EasyChange for optical drives

Packaging information

| | |
|--------------------------------|---|
| Packaging dimension | 467x265x540 mm |
| Max. quantity / pallet | 28 |
| Material - Weight (g) Carton | 1140 g |
| Material - Weight (g) EPS / PS | 180 g |
| Material - Weight (g) PE | appr. 60 g |
| Packaging notes | printed user documentation is bleached in chlorine free process |

Warranty

| | |
|-------------------|---|
| Standard Warranty | 3 years |
| Service level | Bring-In / On-Site Service (depending on country) |

Maintenance and Support Services - the perfect extension

| | |
|--------------------------|---|
| Recommended Service | 5x9, Response Time: Next Business Day |
| Spare Parts availability | 5 years |
| Service Weblink | http://ts.fujitsu.com/Supportservice |

More information

Fujitsu platform solutions

In addition to Fujitsu ESPRIMO E910 E90+, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure-as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu ESPRIMO E910 E90+, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. www.fujitsu.com/fts

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT.

Please find further information at <http://www.fujitsu.com/global/about/environment/>



Copyrights

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see http://ts.fujitsu.com/terms_of_use.html

Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

CONTACT

FUJITSU Technology Solutions
Website: <http://ts.fujitsu.com>
2012-01-20 CE-EN

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions